



VIKAS ecOTECH LTD.

(Formerly Vikas Globalone Ltd.)

www.vikasecotech.com

MATERIAL SAFETY DATA SHEET

Updated on: 1ST January 2016

Addflex

EPOXIDISED SOYABEAN OIL PLASTICIZER & CO-STABILIZER

➤ Product Description:

ADDFLEX, an Epoxidised Soybean Oil, is a High Oxirane Content, Efficient & Compatible Vinyl Additive which essentially functions similar to a polymeric type plasticizer by imparting flexibility and controlling migration due to its high molecular weight. It is also a synergetic, heat & light stabilizing additive that compliments the conventional Metallic Stabilizer systems, facilitating superior processing ability and cost reduction.

➤ PRODUCT IDENTIFICATION:

ESO-603, ESO-601

➤ CAS No.:

8013-07-8

➤ Physical & Chemical Properties:

Particulars		ESO 603	ESO 601	Testing Procedure
	Unit	Standard	Standard	
Appearance		Clear pale yellow liquid	Clear pale yellow liquid	Visual
Color	Gardner	2 Max	2 Max	By Comparator
Odour		Mild	Mild	Olfactory
Oxirane Oxygen	%	6.5 ± 0.1	6.2 ± 0.1	ASTM D1652-73
Acid Value	mg KOH/g	1.0 Max	1.0 Max	IS 548
Iodine Value	g I ₂ /100 g	2.5 ± 1.0 Max	4.0 ± 1.0 Max	Wij's method
Viscosity at 25 °C	cSt	450-500 Max	450-500 Max	Ostwalt Viscometer (U tube)
Specific Gravity at 20 °C		0.985 ~ 0.995	0.980 ~ 0.990	Hydrometer
Moisture Content at 105 °C	%	0.15 Max	0.15 Max	Moisture Analyzer
Refractive Index at 25 °C		1.471-1.475	1.471-1.475	Refractometer
Flash Point	°C	305 Min	295 Min	Flash Point Apparatus (Penskey Marten)

➤ PRODUCT USE:

- Plasticization of all flexible & semi flexible PVC Compounds & Emulsions.
- Supplementing Heat & Light stabilization of Rigid, Semi Rigid & Flexible PVC Compounds.
- Heat Stabilization of CPW plasticizers during the manufacturing process.
- Plasticization of Neoprene, Nitrocellulose and Chlorinated Rubber

➤ POTENTIAL HAZARDS INFORMATION:

✚ FIRE HAZARD:

- BOILING POINT: 150°C
- FLASH POINT: 315°C (DECOMPOSES)
- GENERALLY INFLAMABLE: HOWEVER MAY BURN AT ELEVATED TEMPERATURES.
- EXTINGUISHING MEDIA: WATER, SAND, DRY POWDER.
- COMBUSTION GENERATES CARBON MONOXIDE & CARBON DIOXIDE.

✚ REACTIVITY:

- GENERALLY STABLE / NON REACTIVE.
- INCOMPATIBLE TO: STRONG ACIDS MAY RESULT IN VOLUME EXPANSION.

HEALTH HAZARDS:

- THIS MATERIAL IS NOT LIKELY TO CAUSE ANY HEALTH HAZARDS TO HUMANS. THIS MATERIAL IS PRACTICALLY NON TOXIC EVEN IF SWALLOWED OR ABSORBED THROUGH SKIN.
- AVOID REPEATED OR CONTINUOUS CONTACT WITH SKIN: MAY CAUSE SLIGHT IRRITATION AND / OR SKIN ALLERGY, WEAR GLOVES, AVOID SPILLAGE.
- AVOID EXPOSING EYES TO VAPOURS / MIST: AEROSOLS MAY CAUSE IRRITATION.
- AVOID INHALING VAPOURS: MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT.

FIRST AID MEASURES:

- **EYES:** THOROUGHLY FLUSH EYES WITH WATER, SEEK MEDICAL HELP IF THE IRRITATION PERSISTS.
- **SKIN:** WASH SKIN WITH WATER AND SOAP. SEEK MEDICAL HELP IF THE IRRITATION PERSISTS.
- **INHALATION:** MOVE TO FRESH AIR, SEEK MEDICAL HELP.
- **INGESTION:** DO NOT GIVE LIQUIDS, SEEK MEDICAL HELP IMMEDIATELY.

HANDLING & STORAGE:

▪ HANDLING:

- USE PERSONAL PROTECTIVE DISCRETION, AVOID PROLONGED DIRECT CONTACT.
- KEEP AWAY FROM SPILL WHICH CAN CREATE SLIPPERY CONDITIONS.
- VAPOURS ARE EVOLVED WHEN THE MATERIAL IS HEATED. DO NOT BREATHE VAPOURS / MIST, ARRANGE FOR APPROPRIATE VENTILATION SYSTEM.
- WASH THOROUGHLY AFTER HANDLING, KEEP THE CONTAINERS CLOSED.

▪ **STORAGE:**

- INDOOR STORAGE IS RECOMMENDED, STORE IN COOL, DRY, VENTILATED PLACE.
- STAINLESS STEEL / EPOXY COATED MILD STEEL / INERT MATERIALS ARE RECOMMENDED FOR STORING, TRANSFER OF MATERIAL.
- SHOULD BE HANDLED WITH NORMAL PRECAUTIONS FOR LIQUIDS. REFER TO THE MATERIAL SAFETY DATA SHEET FOR “SAFETY AND HEALTH” INFORMATION.

Disclaimer:

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date. Since the conditions and methods of use of the product and of the information referred to, are beyond our control.

Vikas Ecotech Ltd. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization.

Before handling this material, read and understand the MSDS (Material Safety Data Sheet) for additional information on personal protective equipment and for safety, health and environmental information.